

TATUNG V26MMFJ-ETA

Tatung 26" PAL/DVB-T hybrid SoC packed iDTV



Features

- Integrated PAL/DVB-T tuner
- Common Interface slot for Pay-TV
- MHEG-5 ver 1.06
- NorDig Basic TV Profile
- OAD (Over Air Download) for DVB-T software upgrade
- 3D Comb-filter & 3D De-interlace
- Picture in Picture (PIP); Teletext 500 pages



Items	Model Name	V26MMFJ-ETA (EU model)
Panel	Screen Size	26" TFT-LCD Panel
	Aspect Ratio	16 : 9
	Resolution	1366 x 768 (WXGA)
	Display Area (opening) H x V	575.769 mm x 323.712 mm
	Pixel Pitch	0.4215 mm x 0.4215 mm
	Display colors	16.2M colors
	Contrast Ratio	800 : 1 (typ.)
	Brightness (center)	500 cd / m2 (typ.)
	Viewing Angle (CR>10)	160o Hor. / 150o Ver. (typ.)
	Response Time	Tr =3 ms , Tf =5 ms (typ.)
TV Function	Broadcasting System	Analog : PAL / SECAM Digital : DVB-T
	Receiving Channel	Analog : B / G, D / K, I and L / L' Digital : 54MHz ~ 864MHz
	Sound System	Analog : NICAM / A2 (IGR) Digital : PCM(* /Dolby AC3 /MPEG)
	Resolution	Analog : 625i Digital : 625i
	Data Broadcasting	Teletext 500 pages (FLOF /TOP) , Auto Program Searching (APS)
Video Input	Video Color System	PAL / SECAM / NTSC
	AV1 (scart)	21-pin Scart (RGB / CVBS) x 2
	AV2 (composite)	Composite (RCA jack) x 1
	AV3 (Y/C Signal)	S-Video x 1
	AV4 (component)	Y Pb Pr (720p / 1080i , HDTV ready) x 1
	Video Color System	PAL / SECAM / NTSC
Digital Input	HDMI Connection	HDMI x 2 (HDMI 1.1 Compatible) Audio : Two channel linear PCM 32,44.1 and 48 KHz , 16,20 and 24 bit
PC Input	VGA Connection	D-Sub 15 pin x 1
	Scanning Frequency	fH = 31.5 ~ 60KHz / fV = 56 ~ 70Hz
Audio Input	Audio 1	For Scart (build-in) x 2
	Audio 2	For Composite / S – Video / Component x 1
	Audio 3	For PC x 1
Video Output	SCART 1	TV / CVBS / S-Video x 1
	SCART 2	TV / CVBS / S-Video x 1
Audio Output	Speaker (build-in)	7W + 7W (rms) @ THD < 10% (1W + 1W @ THD < 1%)
	Headphone	3.5mm Jack x 1 (Maximum Output : 1 Vrms)
Feature	OSD Language	English, French , German , Spanish , Italian ,Finnish , Swedish, Dutch, Demark, Norway
	Function Keys	Power , Source , Menu , Up/Down(Channel) , +/--(Volume) , ARC/EXIT .
	Video Performance	3D De-interlace, Canal Plus, Teletext, Aspect Ratio Control (ARC) , Auto Picture Control(APC),Video Enhance, Noise Reduction,
	Audio Performance	Equalizer, Auto Volume Control (AVC),
	Other Control	Sleep Timer
Power	Power Supply	AC 100V ~ 240V , 50 / 60Hz
	Power Consumption	< 120 W
Dimension	W x H x D	675mm * 526m * 210mm
Weight (net)	Without Accessories	13.5kg